

Straight pipe reduction Series 1-2-3



Biosteel part. no.

EX: **SPR** **1** - **42,4** - **33,7** - **1000**

Straight pipe reduction Serie D1 D2 L

				Serie 1		Serie 2		Serie 3		
DN1	d1	DN2	d2	D1	D2	D1	D2	D1	D2	L
25	33,7	20	29,9	90	90	110	110	125	125	1000
32	42,4	20	29,6	90	110	110	125	125	140	1000
32	42,4	25	33,7	90	110	110	125	125	140	1000
40	48,3	25	33,7	90	110	110	125	125	140	1000
40	48,3	32	42,4	110	110	125	125	140	140	1000
50	60,3	32	42,4	110	125	125	140	140	160	1000
50	60,3	40	48,3	110	125	125	140	140	160	1000
65	76,1	40	48,3	110	140	125	160	140	180	1000
65	76,1	50	60,3	125	140	140	160	160	180	1000
80	88,9	50	60,3	125	160	140	180	160	200	1000
80	88,9	65	76,1	140	160	160	180	180	200	1000
100	114,3	65	76,1	140	200	160	225	180	250	1000
100	114,3	80	88,9	160	200	180	225	200	250	1000
125	139,7	80	88,9	160	225	180	250	200	280	1000
125	139,7	100	114,3	200	225	225	250	250	280	1000
150	168,3	100	114,3	200	250	225	280	250	315	1000
150	168,3	125	139,7	225	250	250	280	280	315	1000
200	219,1	125	139,7	225	315	250	355	280	400	1000
200	219,1	150	168,3	250	315	280	355	315	400	1000
250	273,0	150	168,3	250	400	280	450	315	500	1000
250	273,0	200	219,1	315	400	355	450	400	500	1000
300	323,9	200	219,1	315	450	355	500	400	560	1000
300	323,9	250	273,0	400	450	450	500	500	560	1000

Note: Pipe material: P235GH TC1 EN 10217-2
 Other steel grade on request
 Other diameter and length on request
 Free end: 150 mm

biosteel a/s

Algade 35, Grønbjerg · DK-6971 Spjald, Denmark
 +45 4027 8099 · info@biosteel.dk · www.biosteel.dk